

FreshWater® Salt System Ready



FiberCor[®] High-Density Insulation



Exterior Lighting

STRIDE®

HOT SPOT[®] COLLECTION



People	Seating	Jets	Voltage
3 Seats	Lounge	20 Jets	115 V or 230 V

Size

7′ x 5′5″ x 29″ | 213 cm x 165 cm x 74 cm

Water Care

FreshWater® Salt System Ready



HOT SPOT[®] COLLECTION STRIDE





SHELL COLORS*

Alpine White	Pearl	Pebble



Sun

CABINET COLORS*



Almond Havana



LEGENDARY MASSAGE

20 Personalized-Control Jets

- 1 XL Directional Hydromassage jet
- 1 XL Rotary Hydromassage jet
- 3 Directional Hydromassage jets
- 1 Rotary Hydromassage jet
- 14 Directional Precision[®] jets

EASY WATER CARE

Water Care System	FreshWater [®] Salt System Ready	
Filtration System	30 sq. ft., top loading	

LEADING ENERGY EFFICIENCY

Jet Pump	Wavemaster $^{\circledast}$ 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque
Circulation Pump	SilentFlo® 5000 Quiet Continuous Filtration
Heater	No-Fault* 1,000 W / 115 V $$ or 4,000 W / 230 V
Insulation	FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
Cover	WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions 7' x 5'5" x 29" / 213 cm x 165 cm x 74 cm

CAPACITY

Seating Capacity	3 seats
Water Capacity	225 gallons / 850 liters
Weight	570 lbs. / 260 kg dry; 2,975 lbs. / 1,350 kg filled**

ADDITIONAL FEATURES

Smart Spa Technology*	Hot Spring Spas App Powered by the Connected Spa Kit
Cover Lifters*	CoverCradle $\ensuremath{^\circ}$, CoverCradle II, Lift 'n Glide $\ensuremath{^\circ}$, or UpRite $\ensuremath{^\circ}$
Steps*	Hot Spot Collection Step (Almond, Havana, and Storm)
Control System	IQ 2020 [®] with LCD control panel 115 V / 20 amp,*60 Hz (Includes GFCI protected power cord) or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz
Lighting System	Interior: 6 multi-color LED points of light Exterior: 4 multi-color LED points of light

*Optional Accessories

*Actual colors and products may vary from print representation. See dealer to verify.

**Includes water and 7 adults weighing 175 lbs. each.
★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.
◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.