

# HOT SPOT® COLLECTION

## TX



FreshWater®  
Salt System  
Ready



FiberCor®  
High-Density Insulation



Moto-Massage®



*Shown with Alpine White Shell  
and Havana Cabinet.*

<b>People</b>	<b>Seating</b>	<b>Jets</b>	<b>Voltage</b>
2 Seats	Open	11 Jets	115 V or 230 V

**Size**  
6' x 6' x 29" | 183 cm x 183 cm x 74 cm

**Water Care**  
FreshWater® Salt System Ready

# HOT SPOT® COLLECTION



# TX



## SHELL COLORS\*



## CABINET COLORS\*



## COVER COLORS



## LEGENDARY MASSAGE

### 11 Personalized-Control Jets

- 1 Moto-Massage® jet
- 1 Directional Hydromassage jet
- 1 Rotary Hydromassage jet
- 8 Directional Precision® jets

## EASY WATER CARE

- Water Care System** FreshWater® Salt System Ready
- Filtration System** 30 sq. ft., top loading

## LEADING ENERGY EFFICIENCY

- Jet Pump** Wavemaster® 4200; Two-speed, 1.0 HP Continuous Duty, 1.7 HP Breakdown Torque
- Circulation Pump** SilentFlo® 5000 Quiet Continuous Filtration
- Heater** No-Fault® 1,000 W / 115 V or 4,000 W / 230 V
- Insulation** FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas
- Cover** WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

## SIZE

- Dimensions** 6' x 6' x 29" / 183 cm x 183 cm x 74 cm

## CAPACITY

- Seating Capacity** 2 seats
- Water Capacity** 190 gallons / 720 liters
- Weight** 635 lbs. / 290 kg dry; 2,570 lbs. / 1,165 kg filled\*\*

## ADDITIONAL FEATURES

- Smart Spa Technology\*** Hot Spring Spas App Powered by the Connected Spa Kit
- Cover Lifters\*** Lift 'N Glide®
- Steps\*** Hot Spot Collection Step (Almond, Havana, and Storm)
- Control System** IQ 2020® with LCD control panel  
115 V / 15 amp,\* 60 Hz (Includes GFCI protected power cord)  
or 115 V / 30 amp\* or 230 V / 50 amp,\* 60 Hz
- Lighting System** Interior: 4 multi-color LED points of light, dimmable

\*Optional Accessories

\*Actual colors and products may vary from print representation. See dealer to verify.

\*\*Includes water and 7 adults weighing 175 lbs. each.

★Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.